

# Flexus 64

## Stand-Alone Building Entry System

### Operating Features

#### Basic Features

Door-to-handset intercom.  
Directly and exactly replaces old hardwired open-voice entry system.  
Call initiation with single-digit or two-digit keystrokes in a natural fashion.  
Requires no connection to phone wirelines, neither dedicated phone line.

#### Advanced Features

Secure door release with single-digit keystroke.  
Duplex intercom with clear and distinguishable guest's voice for increased security.  
Highly modular design for cost-effectiveness, outstanding reliability and easy maintenance.  
Directly powers doorstrike or interfaces with separate power circuit.  
Single-Module system with modular circuit boards. No separate power supply box to wire to.  
Quick and easy install by handy owner or contractor with snap-in wire attachments and simple tooling.

#### Optional Features

Expandable to 63 unit capacity in a modular fashion.  
Operates with as many as 2 Panels.  
Operable with indoor cordless handsets.

### Specifications

Product code for Flexus Lobby Panel: FLP-2: 2-Button Panel  
FLP-4: 4-Button Panel - FLP-6: 6-Button Panel - FLP-23: Panel with Keypad  
Power Source: 120VAC ~ 50/60 Hz ~ 350 mA  
Output Power to Doorstrike: 24V AC - 240mA  
Maximum voltage feed: 36V AC or 36V DC (unpolarized feed)  
Relay contact ratings: 3A @ 250V AC  
Cabling: 1 twisted pair per suite - CAT5  
Weight: 3 lbs. (FLP-6) - 7 lbs. (FLP-23)  
Operating Environment: 41° F - 95° F



#### FLP-2/FLP-4/FLP-6

Size of faceplate: **W** 5 9/16 in. x **H** 5 9/16 in.  
Size of enclosure: **W** 4 2/16 in. x **H** 4 2/16 in. x **D** 2 3/16 in.  
Finish: Polished Brass (PB) - Brushed Stainless Steel (SS)  
White Powder Coating (WT) - Black Powder Coating (BK)  
Mount: Flush-mount only

#### FLP-23

Size of Faceplate: **W** 6 3/4 in. x **H** 8 2/16 in. - 10 Gauge  
Size of Flush enclosure: **W** 6 1/4 in. x **H** 7 1/2 in. **D** 3 in.  
Size of Surface enclosure: **W** 6 1/4 in. x **H** 7 1/2 in. **D** 3 in.  
Finish: Brushed Stainless Steel - 10 gauge Faceplate  
Mount: Flush-mount (**EAP-23FM**)  
or Surface-mount (**EAP-23SM**)