

Ultimatoll Standard Q-16S-MS

Home Telephone Intercom System



Operating Features

Standard Features

- Room-to-room intercom with standard handsets.
- Distinctive Page on intercom calls.
- Intercom running on existing phone wirelines with daisy-chain or home run wiring.
- Call waiting at door call while phone conversation ongoing.
- Call waiting at incoming phone call during entry intercom conversation.
- Full caller ID pass-thru to handsets.
- Installable by homeowner with minor tooling.

Advanced Features

- Room monitoring via home phones: one-to-one, one-to-many, many-to-many.
- Automatic call pick up and automatic hangup with speakerphones.
- Screened call transfer or direct call transfer.
- Call parking with timeout alert.
- Barge-in over busy extension with privacy from remote line party.
- Three-party conference calls between two household users and one line party.
- Three-party conference calls between three household users.
- Integrates with answering machines for professional voice mail processing
- Emergency mode on power failure.

Optional Features

- Interoperable with multi-unit dwelling intercom system.

Specifications

Power Source: 120VAC ~ 50/60 Hz ~ 35mA
Output Power to Doorstrike: 16VAC - 15W
Weight: 3 lbs.
Operating Environment: 41° F - 95 ° F

Ring Generator: 7 REN maximum
Relay contact ratings: 3A @ 250VAC
Size: **W** 7.187 in. x **H** 10.125 in. x **D** 2.031 in.
Product code: Q-16S-SX
Patented by United States Patent & Trademark Office